

AvaSpec-ULS2048XL SensLine High UV- and NIR-sensitivity back-thinned CCD Spectrometer

Combining exceptional quantum efficiency with high-speed is the value proposition of the AvaSpec-ULS2048XL spectrometer. Unlike many back-thinned CCD spectrometers, which have two dimensional arrays, the ULS2048XL has large monolithic pixels of 14x500 microns with exceptional efficiency in the UV, from 200-400 nm, and the NIR, from 950-1160 nm. The instrument also has an electronic shutter, which enables integration times as low as 2 microseconds. To further enhance sensitivity, a detector collection lens is available which improves sensitivity up to 60% when combined with larger core fibers.

Options include order-sorting filter, to reduce 2nd order effects and purge ports for deep-UV measurements. The AvaSpec-ULS2048XL comes with a wide range of slit sizes, gratings and may be configured with SMA or FC/PC fiber-optic entrance connectors.

The AvaSpec-ULS2048XL is also available in dual or multi-channel versions (up to 10 spectrometers), where all spectra are acquired simultaneously.

Connection to your PC is handled via a USB2-connection, delivering a scan every 2 milliseconds. The instrument comes complete with AvaSoft-basic software, USB cable and an extensive manual, including a quick start guide in four languages.

AvaSpec-ULS2048XL



Technical Data

Optical Bench	ULS, Symmetrical Czerny-Turner, 75 mm focal length
Wavelength range	200 - 1160 nm
Resolution	0.09 -20 nm, depending on configuration (see table)
Stray-light	< 0.3%
Sensitivity	460,000 counts/μW per ms int. time
UV Quantum efficiency	60% (200-300 nm)
Detector	Back-thinned CCD image sensor 2048 pixels
Signal/Noise	450:1
AD converter	16-bit, 1 MHz
Integration time	2 μs - 20 seconds
Interface	USB 2.0 high-speed, 480 Mbps RS-232, 115.200 bps
Sample speed with store to RAM	2.09 ms /scan
Data transfer speed	2.09 ms /scan (USB2) 432 ms / scan (RS-232)
Digital IO	HD-26 connector, 2 Analog in, 2 Analog out, 3 Digital in, 12 Digital out, trigger, synchronization
Power supply	Default USB power, 450 mA. Or with SPU2 external 12VDC, 200 mA
Dimensions, weight	175 x 110 x 44 mm (1 channel), 855 grams

Grating selection table for AvaSpec-ULS2048XL

Use	Useable range (nm)	Spectral range (nm)	Lines/mm	Blaze (nm)	Order code
UV/VIS/NIR	200-1160**	960**	300	300	UA
UV/VIS/NIR	200-1100**	900**	300	300/1000	UNA-DB
UV/VIS	200-850	520	600	300	UB
UV	200-750	250-220*	1200	250	UC
UV	200-650	165-145*	1800	UV	UD
UV	200-580	115-70*	2400	UV	UE
UV	200-400	70-45*	3600	UV	UF
UV/VIS	250-850	520	600	400	BB
VIS/NIR	300-1160**	860**	300	500	VA
VIS	360-1000	500	600	500	VB
VIS	300-800	250-200*	1200	500	VC
VIS	350-750	145-100*	1800	500	VD
VIS	350-640	75-50*	2400	VIS	VE
NIR	500-1050	500	600	750	NB
NIR	500-1050	220-150*	1200	750	NC
NIR	600-1160	350-300	830	800	SI
NIR	600-1160**	560**	300	1000	IA
NIR	600-1160	500	600	1000	IB

* depends on the starting wavelength of the grating; the higher the wavelength, the bigger the dispersion and the smaller the range to select.

** please note that not all 2048 pixels will be used for the useable range

Resolution table (FWHM in nm) for AvaSpec-ULS2048XL

Grating (lines/mm)	Slit size (μm)					
	10	25	50	100	200	500
300	1.40	1.50	2.5	4.8	9.2	21.3
600	0.70 - 0.80*	0.75-0.85*	1.2	2.4	4.6	10.8
830	0.42 - 0.48*	0.50-0.58*	0.93	1.7	3.4	8.5
1200	0.25 - 0.31*	0.37 - 0.43*	0.52-0.66*	1.1	2.3	5.4
1800	0.17 - 0.21*	0.26 - 0.32*	0.34-0.42*	0.8	1.6	3.6
2400	0.12 - 0.18*	0.18 - 0.24*	0.26-0.34*	0.44-0.64*	1.1	2.7
3600	0.09 - 0.12*	0.11 - 0.15*	0.19	0.4	0.8	1.8

* depends on the starting wavelength of the grating; the higher the wavelength, the bigger the dispersion and the better the resolution

Ordering Information

AvaSpec-ULS2048XL-USB2

- Ultra-low Stray-light Fiber-optic Spectrometer, 75 mm AvaBench, 2048 large 500 μm pixel back-thinned CCD detector, USB powered, high-speed USB2 interface, incl. AvaSoft-Basic, USB interface cable.
Specify grating, wavelength range and options

Why is the XL so sensitive?
We're using back-illuminated detectors.
They have the electronics on the backside of the detector,
allowing more light to be caught by the front side.

Options

-SPU2	<ul style="list-style-type: none">• incl. switch for USB power or external power for RS-232
-RS	<ul style="list-style-type: none">• Replaceable slit, see page 41
DCL-UV/VIS-200	<ul style="list-style-type: none">• Quartz Detector Collection Lens (200-1100 nm)
SLIT-XX	<ul style="list-style-type: none">• Slit size, please specify XX = 10, 25, 50, 100, 200 or 500 μm
SLIT-XX-RS	<ul style="list-style-type: none">• Replaceable slit with SMA connector, specify slit size XX=25, 50, 100 or 200 μm. Only in combination with AvaSpec-ULS2048XL-USB2-RS
SLIT-XX-RS-FCPC	<ul style="list-style-type: none">• as SLIT-XX-RS, but with FC/PC connector
OSF-YYY	<ul style="list-style-type: none">• Order-sorting filter for reduction of 2nd order effects, 1 mm thick, please specify YYY= 305, 395, 475, 515, 550 or 600 nm
OSC	<ul style="list-style-type: none">• Order-sorting coating with 600 nm long-pass filter for BB (>350 nm) and VB gratings in AvaSpec-2048XL, recommended with OSF-305
OSC-UA	<ul style="list-style-type: none">• Order-sorting coating with 350 and 600 nm long-pass filter for UA, VA gratings in AvaSpec-ULS2048XL
OSC-UB	<ul style="list-style-type: none">• Order-sorting coating with 350 and 600 nm long-pass filter for UB or BB (<350 nm) gratings in AvaSpec-ULS2048XL
-FCPC	<ul style="list-style-type: none">• FC/PC fiber-optic connector

The grating can only be changed by Avantes.

Therefore, choose your grating wisely.

Our application specialists are available to support you with your choice.

In general, a higher resolution means a lower bandwidth.

By combining multiple spectrometers
in our AvaSpec-Dual or rack-mountable versions,
you can create one virtual spectrometer with high-resolution
and high bandwidth.