




GREEN LASER MODULE



Modle # : JPM-1-6(8mm)

Features

- Structure : Diode pumped solid-state green lasers.
- Output power : <1 mW
- Operating temperature : 15~35°C

Applications

- Presenter
- Laser pointer

Absolute maximum ratings

| Parameter | Symbol | Rating | Unit |
|-----------------------|--------|--------|------|
| Operating current | Iop | 300 | mA |
| Operating temperature | Topr | 15 ~35 | °C |
| Storage temperature | Tstg | 0~ +50 | °C |

Specifications 1) 2)

| Parameter | Symbol | Condition | Min | Typ | Max | Unit |
|-----------------------------|-----------------|------------------|-----|------|-----|--------|
| Supply voltage | Vcc | | 2.4 | - | 3.4 | V |
| Wavelength | λP | | 522 | 532 | 542 | nm |
| Output power | P ₀ | | 0.3 | - | 0.9 | mW |
| Power stability | △P ₀ | Topr=15 ~ +35°C | -20 | | +20 | % |
| Operating Current | - | | 200 | - | 300 | mA |
| Laser beam deflection angle | - | In 50cm location | -3 | 0 | 3 | degree |
| Beam divergence | 2θr | | - | 1.55 | - | mrad |

1) Initial values 2)Each value is measured by using our measuring instrument 3)△1: The distance from laser beam window

Beam spot spec

- 5m diameter<12.5mm(不包含光量、雜光、拖尾)

Remark

- 出貨測試 15 秒內,以最高值得到功率、電流
- 測試環境溫度:20~30°C ± 2°C ; 濕度: 40~60%
- 按鍵可拿掉，彈簧可改接線

Kokyo

株式会社 光饗

Email : info@sympotony.com
Web : https://www.sympotony.com/