

AvaSpec-ULS3648 StarLine High-resolution Fiber-optic Spectrometer

When you're looking for high-resolution, then take a look at the AvaSpec-ULS3648. Featuring an electronic shutter, it can support integration times as short as 10 microseconds, making it also ideal for CW laser measurements.

Options include order-sorting filters to prevent 2nd order effects, deep-UV detector coating for better sensitivity in the deep-UV-range, and a detector collection lens to enhance overall sensitivity. Also, a wide range of slit sizes, gratings and fiber-optic entrance connectors are available.

Configurations with two to ten channel spectrometers are available. These give you the possibility for multiple simultaneous

readouts or higher optical resolution in which several spectrometers are arrayed with each covering a short range with high-resolution. For more information, see pages 62 and 63.

The connection to your computer is done through USB2 at 480 Mbps. This translates into 3.7 ms per scan data transfer speed. Of course it's supplied with AvaSoft-Basic, USB cable and an extensive manual, including a quick start guide in four languages.

AvaSpec-ULS3648



Technical Data

| | |
|---------------------------------------|--|
| Optical Bench | ULS Symmetrical Czerny-Turner, 75 mm focal length |
| Wavelength range | 200 - 1100 nm |
| Resolution | 0.05 -20 nm, depending on configuration (see table) |
| Stray-light | 0.38-0.53%, depending on the grating |
| Sensitivity | 160,000 counts/μW per ms integration time |
| Detector | CCD linear array, 3648 pixels |
| Signal/Noise | 350:1 |
| AD converter | 16-bit, 1 MHz |
| Integration time | 10 μs - 10 minutes |
| Interface | USB 2.0 high-speed, 480 Mbps RS-232, 115.200 bps |
| Sample speed with store to RAM | 3.7 ms /scan |
| Data transfer speed | 3.7 ms /scan (USB2) 750 ms/scan (RS-232) |
| Digital IO | HD-26 connector, 2 Analog in, 2 Analog out, 3 Digital in, 12 Digital out, trigger, synchronization |
| Power supply | Default USB power, 350 mA Or with SPU2 external 12VDC, 150 mA |
| Dimensions, weight | 175 x 110 x 44 mm (1 channel), 716 grams |

Grating selection table for AvaSpec-ULS3648

| Use | Useable range (nm) | Spectral range (nm) | Lines/mm | Blaze (nm) | Order code |
|------------|--------------------|---------------------|----------|------------|------------|
| UV/VIS/NIR | 200-1100** | 900** | 300 | 300 | UA |
| UV/VIS/NIR | 200-1100** | 900** | 300 | 300/1000 | UNA-DB |
| UV/VIS | 200-850 | 520 | 600 | 300 | UB |
| UV | 200-750 | 250-220* | 1200 | 250 | UC |
| UV | 200-650 | 165-145* | 1800 | UV | UD |
| UV | 200-580 | 115-70* | 2400 | UV | UE |
| UV | 200-400 | 70-45* | 3600 | UV | UF |
| UV/VIS | 250-850 | 520 | 600 | 400 | BB |
| VIS/NIR | 300-1100** | 800** | 300 | 500 | VA |
| VIS | 360-1000 | 500 | 600 | 500 | VB |
| VIS | 300-800 | 250-200* | 1200 | 500 | VC |
| VIS | 350-750 | 145-100* | 1800 | 500 | VD |
| VIS | 350-610 | 75-50* | 2400 | VIS | VE |
| NIR | 500-1050 | 500 | 600 | 750 | NB |
| NIR | 500-1050 | 220-150* | 1200 | 750 | NC |
| NIR | 600-1100 | 350-300 | 830 | 800 | SI |
| NIR | 600-1100** | 500** | 300 | 1000 | IA |
| NIR | 600-1100 | 500 | 600 | 1000 | IB |

* depends on the starting wavelength of the grating; the higher the wavelength, the bigger the dispersion and the smaller the range to select.

** please note that not all 3648 pixels will be used for the useable range

Resolution table (FWHM in nm) for AvaSpec-ULS3648

| Grating (lines/mm) | Slit size (μm) | | | | | |
|--------------------|----------------|--------------|------------|------------|------|------|
| | 10 | 25 | 50 | 100 | 200 | 500 |
| 300 | 0.60 - 0.70* | 1.10-1.30* | 2.20-2.40* | 4.60 | 9.00 | 20.0 |
| 600 | 0.30 - 0.36* | 0.58-0.68* | 1.17 | 2.20 | 4.50 | 10.0 |
| 830 | 0.25 | 0.48 | 0.93 | 1.70 | 3.40 | 8.0 |
| 1200 | 0.14 - 0.18* | 0.30 | 0.62 | 1.08 | 2.20 | 5.0 |
| 1800 | 0.09 - 0.11* | 0.18 | 0.36-0.40* | 0.78 | 1.50 | 3.7 |
| 2400 | 0.07 - 0.09* | 0.13 - 0.15* | 0.26-0.32* | 0.52-0.64* | 1.10 | 2.7 |
| 3600 | 0.05 - 0.06* | 0.10 | 0.19 | 0.40 | 0.80 | 2.0 |

* depends on the starting wavelength of the grating; the higher the wavelength, the bigger the dispersion and the better the resolution

Ordering Information

AvaSpec-ULS3648-USB2

- Fiber-optic Spectrometer, 75 mm AvaBench, 3648 pixel CCD detector, USB powered, high-speed USB2 interface, incl. AvaSoft-Basic, USB interface cable.
- Specify grating, wavelength range and options

Options

| | |
|------------------------|--|
| -SPU2 | • incl. switch for USB powered or external power for RS-232 |
| -RS | • Replaceable slit, see page 41 |
| DUV | • Deep-UV detector coating >150 nm |
| DCL-UV/VIS-200 | • Quartz Detector Collection Lens (200-1100 nm) |
| SLIT-XX | • Slit size, please specify XX = 5, 10, 25, 50, 100, 200 or 500 μm |
| SLIT-XX-RS | • Replaceable slit with SMA connector, specify slit size XX=25, 50, 100 or 200 μm . Only in combination with AvaSpec-ULS3648-USB2-RS |
| SLIT-XX-RS-FCPC | • as SLIT-XX-RS, but with FC/PC connector |
| OSF-YYY | • Order-sorting filter for reduction of 2nd order effects please specify YYY= 305, 395, 475, 515, 550 or 600 nm |
| OSC | • Order-sorting coating with 600 nm long-pass filter for BB (>305 nm) and VB gratings in AvaSpec-ULS3648, recommended with OSF-305 |
| OSC-UA | • Order-sorting coating with 350 and 600 nm long-pass filter for UA, VA gratings in AvaSpec-ULS3648 |
| OSC-UB | • Order-sorting coating with 350 and 600 nm long-pass filter for UB or BB (<350 nm) gratings in AvaSpec-ULS3648 |
| -FCPC | • FC/PC fiber-optic connector |

The grating can only be changed by Avantes.

Therefore, choose your grating wisely.

Our application specialists are available to support you with your choice.

In general, a higher resolution means a lower bandwidth.

By combining multiple spectrometers
in our AvaSpec-Dual or rack-mountable versions,
you can create one virtual spectrometer with high-resolution
and high bandwidth.