

## Mini Size Polarization Insensitive Isolator

<b>Features</b>	
Wide Operating Wavelength High isolation & Low insertion loss & Low PDL Mini Size	
<b>Application</b>	
EDFA Transmitters WDM & DWDM System Testing instruments	

### Specifications

Type Parameter	Single Grade		Dual Grade	
	P	A	P	A
Operating wavelength (nm)	1310, 1550			
Bandwidth (nm)	±15			
Peak isolation (dB)	40	38	50	48
Isolation (at 23□) (dB)	≥28	≥26	≥42	≥40
Typ. Insertion Loss (at 23□)	0.4	0.5	0.5	0.6
Insertion Loss (at -5 ~ +70 □)	≤0.6	≤0.7	≤0.70	≤0.80
PDL at 23□ (dB)	≤0.1	≤0.15	≤0.1	≤0.15
PMD (ps)	≤0.25	≤0.25	≤0.25	≤0.25
Return Loss (dB)	≥55/50	≥55/50	≥55/50	≥55/50
Power handling (mW)	≤300			
Fiber Type	SMF-28e			
Operating temperature (□)	-5 ~ +70			
Storage temperature (□)	-40 ~ +80			
Dimensions (mm)	φ3.0×L25 or φ3.0×L22			

\*Above specifications are for devices without the connectors.

### Packing Dimensions



### Ordering Information

IS	Type	Grade	Wavelength	Pigtail Type	Fiber Type	Length	Connector	Package size
	S= Single stage D = Dual Stage	P A	1310 1550 1	250=250um bare fiber 900=900um loose tube	1=SMF-28e	1= 1m	NE=None FA=FC/APC FC=FC/UPC SA=SC/APC SC=SC/UPC LC=LC/UPC LA=LC/APC XX=Other	3x25 3x22